

LIST OF FIGURES

1.1 Methods of Dehumidification.....	2
1.2 Honeycomb Structure of Desiccant Wheel	16
1.3 Rotary Wheel for Counter Flow of Ventilation flow and Exhaust flow	16
2.1 Air Conditioning Processes	20
2.2 Thermal Processes	20
2.3 Principle of Desiccant Cooling.....	21
2.4 Psychrometric Chart Illustrating the Principle of Desiccant Cooling	22
2.5 Typical Desiccant Dehumidifier Unit	24
2.6 Rotary Desiccant Wheel	25
3.1 Physical Descriptions and Coordinate System of the Problem	27
3.2 Zoomed in View of Hypothetical Layer of Air Next to Desiccant	31
4.1 Mass Transfer Augmentation Parameter	38
4.2 Air Humidity Ratio along the Desiccant Thickness for Air mass flow rate of 34.3 kg/hr. and Air Velocity of 1.56 m/s.....	38
4.3 Air Humidity Ratio along the Desiccant Thickness for Air mass flow rate of 36.4 kg/hr. and Air Velocity of 1.66 m/s.....	39
4.4 Air Humidity Ratio along the Desiccant Thickness for Air mass flow rate of 49.4 kg/hr. and Air Velocity of 2.25 m/s.....	40
4.5 Air Humidity Ratio along the Desiccant Thickness for Air mass flow rate of 74.3 kg/hr. and Air Velocity of 3.38 m/s.....	40
4.6 Air Humidity Ratio along the Desiccant Thickness for Air mass flow rate of 100.3	

kg/hr. and Air Velocity of 4.57 m/s.....	41
4.7 Air Humidity Ratio along the Desiccant Thickness for Different Values of Air mass flow rates and Air Velocities.....	41
4.8 Water Desiccant Content along the Desiccant Thickness for Air mass flow rate of 34.3 kg/hr. and Air Velocity of 1.56 m/s.....	42
4.9 Water Desiccant Content along the Desiccant Thickness for Air mass flow rate of 36.4 kg/hr. and Air Velocity of 1.66 m/s.....	42
4.10 Water Desiccant Content along the Desiccant Thickness for Air mass flow rate of 49.4 kg/hr. and Air Velocity of 2.56 m/s.....	43
4.11 Water Desiccant Content along the Desiccant Thickness for Air mass flow rate of 74.3 kg/hr. and Air Velocity of 3.38 m/s.....	43
4.12 Water Desiccant Content along the Desiccant Thickness for Air mass flow rate of 100.3 kg/hr. and Air Velocity of 4.57 m/s.....	44
4.13 Dehumidification Rate versus Dry Bulb Temperature for Different RH values and Air mass flow rate of 34.3 kg/hr. and Air Velocity of 1.56 m/s.....	45
4.14 Dehumidification Rate versus Dry Bulb Temperature for Different RH values and Air mass flow rate of 36.4 kg/hr. and Air Velocity of 1.66 m/s.....	45
4.15 Dehumidification Rate versus Dry Bulb Temperature for Different RH values and Air mass flow rate of 49.4 kg/hr. and Air Velocity of 2.25 m/s.....	46
4.16 Dehumidification Rate versus Dry Bulb Temperature for Different RH values and Air mass flow rate of 74.3 kg/hr. and Air Velocity of 3.38 m/s.....	46
4.17 Dehumidification Rate versus Dry Bulb Temperature for Different RH values and Air mass flow rate of 100.3 kg/hr. and Air Velocity of 4.57 m/s.....	47
4.18 Dehumidification Rate versus Relative Humidity values for Air mass flow rate of	

34.3 kg/hr and Air Velocity of 1.56 m/s.....	48
4.19 Dehumidification Rate versus Relative Humidity values for Air mass flow rate of 36.4 kg/hr. and Air Velocity of 1.66 m/s.....	48
4.20 Dehumidification Rate versus Relative Humidity values for Air mass flow rate of 49.4 kg/hr. and Air Velocity of 2.25 m/s.....	49
4.21 Dehumidification Rate versus Relative Humidity values for Air mass flow rate of 74.3 kg/hr. and Air Velocity of 3.38 m/s.....	49
4.22 Dehumidification Rate versus Relative Humidity values for Air mass flow rate of 100.3 kg/hr. and Air Velocity of 4.57 m/s.....	50
4.23 Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate for Relative Humidity of 20 %.....	51
4.24 Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate for Relative Humidity of 40 %.....	51
4.25 Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate for Relative Humidity of 60 %.....	52
4.26 Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate at Relative Humidity of 90 %.....	52
4.27a Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate for Relative Humidities of 10 % to 90 %.....	53
4.27b Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate for Relative Humidities of 10 % to 90 % (Another View).....	54
4.28 Optimum Dehumidification Rate versus Dry Bulb Temperature and Mass Flow Rate at Relative Humidities of 10 % to 90 %.....	54

4.29	The Relative Humidity Polynomial Coefficient C_1	57
4.30	The Relative Humidity Polynomial Coefficient C_2	58
4.31	The Relative Humidity Polynomial Coefficient C_4	58
4.32	The Relative Humidity Polynomial Coefficient C_6	59
4.33	The Relative Humidity Polynomial Coefficient C_7	59
4.34	The Relative Humidity Polynomial Coefficient C_8	60

NOMENCLATURE

A_{ch}	Cross-sectional area of the desiccant channel
U_{ch}	Air flow speed inside channel
U_f	Air flow speed at the desiccant wheel face
$C_{b,m}$	Mean specific heat for desiccant bed (J/kg _d . K)
C_a	Mean specific heat for moist air (J/kg _a . K)
D_H	Hydraulic diameter (m)
f_c	Actual mass and heat transfer area / unit volume of the air gap (m ⁻¹)
G_{ch}	Superficial mass flux (kg/m ² . s)
h_w	Heat of wetting (J/kg)
i_a	Specific enthalpy of the moist air (J/kg)
i_d	Specific enthalpy of the desiccant bed (J/kg)
K_m	Coefficient of mass transfer (kg . m ² /s)
L	Passage length (m)
$\frac{m}{L}$	Air mass flow rate per channel (kg/hr)
q_z	Specific energy transfer rate through the boundary (w/m ³)
T	System equilibrium temperature (°K)
t_w	Wall temperature (°C)
t	Air temperature (°C)
W	Water content of desiccant (kg / kg)
$\frac{V}{V_p}$	Packing filling factor
Φ	Relative humidity
ρ_a	Density of air (kg/m ³)
ρ_d	Density of dry desiccant material (kg/m ³)
τ	Time (sec.)

Subscript

<i>a</i>	Air
<i>a, d</i>	Dry air
<i>d</i>	Desiccant
<i>d, d</i>	Dry desiccant
<i>d, w</i>	Wetted desiccant
<i>b</i>	Desiccant bed
<i>ch</i>	Air channel
<i>s</i>	Cross sectional area of the substrate carrying material
<i>w, l</i>	Water (liquid)
<i>w, v</i>	Water (vapor)