

## LIST OF FIGURES

Figure 2.1	Waste tires in an open area .....	7
Figure 2.2	Components of regular car tire .....	8
Figure 2.3	The mechanical grinding process. ....	9
Figure 2.4	20-30 mm rubber chips .....	10
Figure 2.5	Rubber of 10 mm size .....	11
Figure 2.6	Crumb rubber at different sizes .....	12
Figure 2.7	Different sizes of rubber fibers. ....	13
Figure 2.8	The uses of waste tires in the U.S market .....	14
Figure 2.9	The applications of ground rubber in the U.S in 2011 .....	16
Figure 2.10	Examples on some products from waste rubber .....	17
Figure 2.11	The slump values of different rubber contents [30] .....	19
Figure 2.12	The effect of rubber surface treatment on slump values [30] .....	20
Figure 2.13	The relationship between the density and rubber/cement ratio (by mass) [1].....	21
Figure 2.14	The compressive strength for rubberized concrete [4].....	22
Figure 2.15	Compressive strength for rubberized concrete [21] .....	23
Figure 2.16	Flexural strength results by Hai Huynh for ground rubber mixes and 4.75mm fibrous rubber [22] .....	24
Figure 2.17	Stress-strain curves for control concrete and concrete with 7.5% crumb rubber as a replacement of fine aggregate [14] .....	24
Figure 2.18	The damping ratio of normal concrete and rubberized concrete with 20% rubber content [38] .....	25
Figure 2.19	Flexural strength of concrete containing coated rubber chips [5].....	28
Figure 2.20	Compressive strength test samples of the rubberized concrete containing rubber particles coated with cement paste .....	28
Figure 2.21	Compressive strength test samples of the rubberized concrete containing plain rubber particles .....	29
Figure 2.22	Compressive strength for different treatment methods [30] .....	29
Figure 2.23	Tensile strength for different treatment methods [30].....	30
Figure 3.1	The sieve analysis of sand .....	36
Figure 3.2	The sieve analysis of Pink limestone .....	36
Figure 3.3	4mm Crumb rubber .....	37
Figure 3.4	Fibrous rubber separated into different sizes .....	38
Figure 3.5	Fibrous rubber used in the study .....	39
Figure 3.6	Drop weight test equipment .....	41
Figure 3.7	Parameters calculated for evaluation of flexural toughness .....	44
Figure 3.8	Arrangement of specimen for Flexural toughness test .....	45
Figure 3.9	Types of rubber particles .....	48
Figure 3.10	The temperature gradient through the sample .....	51
Figure 3.11	Configuration of Lee test of bad conductors .....	51
Figure 3.12	Rubberized concrete specimen of Lee test .....	52
Figure 3.13	The temperature - time relation for calculation of Q .....	53
Figure 3.14	Configuration of sound attenuation test .....	54
Figure 4.1	Factors affecting compressive strength after 7 days .....	59
Figure 4.2	Factors affecting compressive strength after 28 days .....	60
Figure 4.3	The contribution of each factor on cube concrete compressive strength after 7 days .....	61
Figure 4.4	The contribution of each factor on cube concrete compressive strength after 28 days .....	62

Figure 4.5	Effect of two factor interaction at different factor levels after 28 days on cube compressive strength .....	64
Figure 4.6	Effect of two factor interaction at different factor levels after 28 days on cube compressive strength .....	65
Figure 4.7	Factors affecting slump test results .....	78
Figure 4.8	The contribution of each factor on slump test results .....	79
Figure 4.9	Effect of two factor interaction at different factor levels on slump test results .....	81
Figure 4.10	Factors affecting static modulus of elasticity test results .....	84
Figure 4.11	The contribution of each factor on static modulus of elasticity .....	86
Figure 4.12	Effect of two factor interaction at different factor levels on static modulus of elasticity .....	88
Figure 4.13	Factors affecting first crack impact resistance .....	92
Figure 4.14	Factors affecting failure impact resistance .....	93
Figure 4.15	The contribution of each factor on first crack impact resistance .....	94
Figure 4.16	The contribution of each factor on failure impact resistance .....	94
Figure 4.17	Effect of two factor interaction at different factor levels on first crack impact resistance .....	97
Figure 4.18	Effect of two factor interaction at different factor levels on failure impact resistance .....	98
Figure 4.19	Factors affecting Flexural toughness .....	102
Figure 4.20	Factors affecting Flexural toughness .....	103
Figure 4.21	The contribution of each factor on Flexural strength .....	105
Figure 4.22	The contribution of each factor on Flexural toughness .....	105
Figure 4.23	Effect of two factor interaction at different factor levels on flexural strength .....	107
Figure 4.24	Effect of two factor interaction at different factor levels on flexural toughness .....	108
Figure 4.25	Factors affecting abrasion resistance .....	112
Figure 4.26	The contribution of each factor on abrasion resistance .....	113
Figure 4.27	Effect of two factor interaction at different factor levels on abrasion resistance .....	115
Figure 5.1	Thermal conductivity (K) for conventional concrete and rubberized concrete at different percentages of sand replacement by rubber particles .....	119
Figure 5.2	The correlation between the thermal conductivity and density.....	120
Figure 5.3	Attenuation coefficient of normal concrete and rubberized concrete at different percentages of sand replacement by rubber .....	121
Figure 5.4	Density at different percentages of sand replacement by rubber .....	122
Figure 5.5	Water absorption at different percentages of sand replacement by rubber .....	123
Figure 5.6	Cube compressive strength at different percentages of sand replacement by rubber.....	124
Figure 5.7	Drop weight test results at different rubber contents .....	125
Figure 5.8	Number of blows for crack propagation.....	126
Figure 5.9	Flexural strength at different percentages of sand replacement by rubber.....	127
Figure 5.10	Flexural maximum deflections at different percentages of sand replacement by rubber.....	128
Figure 5.11	Thermal conductivity (K) for rubber-cement and rubber-epoxy composites.....	129
Figure 5.12	Attenuation coefficients of rubber-cement and rubber-epoxy composites.....	131
Figure 5.13	Dry unit weight of rubber-cement and rubber-epoxy composites.....	132
Figure 5.14	The specimens of rubber-cement and rubber-epoxy composites .....	133
Figure 5.15	The shape of failure under compression load for rubber-cement composites.....	134
Figure 5.16	The shape of failure under compression load for rubber-epoxy composites.....	135
Figure 5.17	The stress-strain curve for rubber-cement composites.....	136
Figure 5.18	The stress-strain curve for rubber-epoxy composites.....	136

Figure 5.19 Rubber-epoxy specimens after the first cycle of loading .....	137
Figure 5.20 The loading cycles of rubber-epoxy composite with Fiber 8 .....	137
Figure 5.21 The loading cycles of rubber-epoxy composite with Fiber 4 .....	138
Figure 5.22 Rubber epoxy composite with Fiber 8 after one loading cycle (a) and eight cycles of loading (b) .....	138