

List of Figures

1.1	Cognitive radio network	2
2.1	The system model.	14
2.2	Markov Chain model of the PU queue evolution.	16
2.3	The SU throughput for the interference-based model and the collision-based model for $P_p^{o'} = P_s^{o'} = 0.22$ under PU queue stability constraint.	24
2.4	The SU throughput for the interference-based model and the collision-based model for $P_p^{o'} = P_s^{o'} = 0.8$ under PU queue stability constraint.	25
2.5	The SU access probabilities for the interference-based model for $P_p^{o'} = P_s^{o'} = 0.22$ under PU queue stability constraint.	25
2.6	The SU access probabilities for the interference-based model for $P_p^{o'} = P_s^{o'} = 0.8$ under PU queue stability constraint.	26
2.7	The SU throughput for the interference-based model and the collision-based model for $P_p^{o'} = P_s^{o'} = 0.22$ under average PU packet delay constraint.	26
2.8	The SU throughput for the interference-based model and the collision-based model for $P_p^{o'} = P_s^{o'} = 0.8$ under average PU packet delay constraint.	27
2.9	The average PU packet delay for $P_p^{o'} = P_s^{o'} = 0.1$ when the average PU packet delay constraint is set to 2 slots.	27
2.10	The SU access probabilities for the interference-based model for $P_p^{o'} = P_s^{o'} = 0.22$ under average PU packet delay constraint of two slots.	28
2.11	The SU throughput for the interference-based model and the collision-based model for $\lambda_p = 0.4$	28
3.1	System model	32
3.2	Queue 1, Q_1 , Markov chain model for Dominant System 1.	33
3.3	The stability regions for Random Access with Feedback, and Time Division schemes.	36
3.4	Batteries Markov chain model.	37
3.5	packet queues Markov chain model.	38
3.6	The stability regions for Random Access with Feedback, and Random Access with Feedback and Energy harvesting in B_2 for $\delta_2 = 0.8$	40
3.7	The stability regions for Random Access with Feedback, and Random Access with Feedback and Energy harvesting in B_1 for $\delta_1 = 0.8$	41

List of Figures

3.8	The stability regions for Random Access with Feedback, and Random Access with Feedback and Energy harvesting in both batteries for $\delta_1 = \delta_2 = 0.8$.	44
3.9	The stability regions for Random Access with Feedback, and Random Access with Feedback and Energy harvesting in both batteries for $\delta_1 = \delta_2 = 0.6$.	44
4.1	System model	47
4.2	Maximum achievable λ_p versus p_q for $p_a = 0.5$ and $\delta = 0.42$	53
4.3	Maximum achievable λ_p versus p_a for $p_q = 0.5$ and $\delta = 0.42$	53
4.4	Maximum achievable λ_s versus p_q for $p_a = 0.5$ and $\delta = 0.42$	54
4.5	Maximum achievable λ_s versus p_a for $p_q = 0.5$ and $\delta = 0.42$	54
4.6	The stability boundaries for our system with $\delta = 0.2, 0.5$ and 0.8 and the system with no energy limitation.	56
4.7	Comparison between simulation results and theoretical results of the PU delay at $p_a = 1, p_q = 0.5$ and $\delta = 0.7$	59
4.8	Comparison between simulation results and theoretical results of the SU delay at $p_a = 1, p_q = 0.5$ and $\delta = 0.7$	59